

AHL-3-3,2 Abstandhalter





Merkmale

- einseitig Rastverriegelung
- einseitig zur Durchsteckmontage (fast bündiger Abschluss)
- für Leiterplattenstärke 1,5 mm, Loch-Ø = 3,2 mm
- für Gehäusestärke 3,0 mm, Loch-Ø = 5,0 mm
- Material: Polyamid 6.6, UL94HB
- temperaturbeständig bis ca. + 110° C
- Farbe: schwarz

Abmessungen

► Einheit = mm



Art.-Nr.	A (mm)
100 70 03	3,2
100 70 04	4,0
100 70 05	5,0
100 70 06	6,0
100 70 07	7,0
100 70 08	8,0
100 70 09	9,0
100 70 10	10,0
100 70 11	11,0
100 70 12	12,0
100 70 13	13,0
100 70 14	14,0
100 70 15	15,0
100 70 16	16,0
100 70 17	17,0
100 70 18	18,0
100 70 19	19,0

Art.-Nr.	A (mm)
100 70 20	20,0
100 70 21	21,0
100 70 22	22,0
100 70 23	23,0
100 70 24	24,0
100 70 25	25,0
100 70 26	26,0
100 70 27	27,0
100 70 28	28,0
100 70 29	29,0
100 70 30	30,0
100 70 31	31,0
100 70 32	32,0
100 70 33	33,0
100 70 34	34,0
100 70 35	35,0
100 70 36	36,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0

